

Gertec SP-1100-1




Application areas :

- Special foundation engineering, tunneling (bored pile, cut-off wall, jet grouting).
- Biogas production
- Chemical industry
- Ceramic and porcelain industry

Pumping of :

- Bentonite slurries, drilling fluids, sealing wall slurries, groundwater, mortar, slurries, dirty water, cement, fly ash or other solid-contaminating slurries
- Return suspensions
- Biomasses, press water



Technical data :

Flow rate	max. 48	m ³ /h
Discharge pressure	max. 8	bar
Suction lift	max. 8	m
Solids grain size	max. 32	mm
Medium temperature	50	°C
Nominal diameter of hose	100	mm
Pump speed	37	upm
Suction connection	Storz A	4" standard coupling DIN 14307, alternatively 4" AG, flange DN100 PN16
Pressure connection	Storz A	4" standard coupling DIN 14307, alternatively 4" AG, flange DN100 PN16
Power connection	CEE-plug	63 A, 5-pole
Power input	22	kW
Voltage	400	V; 50 Hz
Dimensions	1,57 x 1,52 x 1,63	m (L x W x H)
Weight	approx.1500	kg

10/02/2023

Characteristics :

- Dry running
- Self-priming
- Reversible
- Low pulsation
- High productivity
- High operating reliability
- Easy wear compensation of the hose pump via eccentric adjustment
- Central lifting eye for crane handling
- Forklift handling from long and transverse side, lift truck handling from long side

Features :

- Steel frame with forklift pockets and central lifting eye
- Pump housing with pivoting housing cover
- Pump drive with reinforced bearing
- Pump rotor with rotatable mounted pressure rollers including eccentric adjustment
- Hose rupture detection
- Vacuum unit to support suction capability
- Pulsation damper reduces the flow rate pulsation
- Pressure switch-off (safety device)
- Remote control connection arranged
- Operating manual and spare parts list
- Electrical function and power control with the following display and control elements:
 - Main switch ON/OFF
 - Pump ON/OFF
 - Vacuum pump ON/OFF
 - Selector switch reversing operation (forwards/backwards)
 - Selector switch on-site/remote control
 - Display hose rupture detection
 - Display combined fault

Rental fee : 180 €/day

Included option : Spare inside hose

Possible options : Suction filter + suction/discharge hoses (2 X 10 m) : 50 €/day



Chaussée de Bruxelles 206 – 7090 Braine-le-Comte – Belgium
Tel : +32 (0)67 55 21 13 – info@swalmec.be – [www. Swalmec.be](http://www.Swalmec.be)